

STANDARD SPECIFICATIONS



CODES

All homes are built to meet or exceed the following codes:

- International Residential Code
- · Uniform Plumbing Code
- Uniform Mechanical Code
- · National Electric Code
- State Energy Code
- State Building Code

FLOOR SYSTEM

- 2 x 10 Joists at 16" on center for up to 14'6" wide
- 2 x 12 Joists at 16" on center for over 14'6" wide
- · Double Rim Joists on outside edges
- · Triple Center Rim Joists with joist hangers
- Thermax Insulated Rim Boards for continuous insulation
- End Floor Bridging Floor Supports for added strength
- 3/4" Tongue and Groove OSB Sub-Flooring (Glued and Nailed)

WALL SYSTEMS

Exterior

- 2 x 6 studs at 16" on center with 2 x 6 double top plate
- 1/2" gypsum board on walls screwed and glued
- 7/16" OSB to all exterior walls stapled and glued
- 1/8" Brace Board to inside of exterior and mating wall for additional strength and rigidity
- · Continuous sill seal for increased insulation
- Double 2 x 10 headers over openings
- Intersecting interior walls secured with lag screws
- Drywall on mating wall screwed and glued
- 8' flat ceiling height

Interior

- 2 x 4 Studs at 16" on center
- 2 x 6 Studs at 16" on center for plumbing wall only
- 1/2" Gypsum Board, Screwed as per code requirements

ROOF SYSTEM

- 60# or 40# Load Engineered Trusses at 24" on center
- 5/12 Roof Pitch
- Timberline Architectural Asphalt Shingle
- 30# Synthetic Underlayment
- 7/16" OSB Exterior Sheathing
- 16" Overhang with 2 x 6 Sub-Fascia
- EDCO Metal Soffit & Fascia
- · Ice Dam Protection (ice and water shield), 6' up roof
- Steel Roof Edge
- 5/8" sheetrock on ceiling adhered with foam spray glue to increase strength and minimize possible cracking
- Fold-up end gable trusses with building wrap

INSULATION

- Walls R-21
- Roof R-50
- Rim R-21
- Batt Insulation at Energy Heel of Truss
- · All penetrations in exterior and mod line walls sealed

PLUMBING & HEATING

- Pex water supply lines with shut off valves run to central location on bottom of joists.
- PVC Drain, Waste and Vent Piping stubbed through floor for on site connection
- Radon Venting installed through walls, to be connected on site
- 8" Deep Two Bowl Stainless Steel Kitchen Sink
- · China Lavatory Vanity Sinks & Stools
- Moen Single Lever Chrome Faucets Throughout
- · One Piece Fiberglass Tub/Shower Unit
- HVAC boots and registers installed per code
- 1.6 Gallon Water Efficient Toilets
- Ice maker box behind refrigerator/Dryer vent box behind dryer
- · Revent pipe to all basement homes
- Exterior Frost Free faucet installed at kitchen location

ELECTRICAL

- 200 Amp, 40 Space, Electrical Service panel
- · Modern Cordless Door Chime at front door
- TV/Phone jacks strategically placed in up to five locations throughout the home, rough-in only with pull wires
- Standard Satin Nickel contemporary lighting package
- · Exterior GFCI Outlet
- All boxes mounted to studs
- Smoke and Carbon Dioxide Detectors per code
- Bath fan with LED Light, 80 CFM 1.5 Sones, Energy Star Certified
- · LED down light over tub/shower and kitchen sink

WINDOWS, DOORS & CLADDING

- Low E double hung windows built to meet Energy Star® standards for superior performance
- Double 4 Vinyl Siding .046" thickness
- Premium Select Steel 2 Panel insulated Entrance door, primed white with a smooth surface ideal for painting
- Bayerbuilt painted 6-panel solid core interior doors prefinished using a water-based stain with a water-based UV seal and top coat for a durable, scratch-resistant finish
- Durable Satin Nickel Door Hardware Keyed knob provided at entrance door, privacy knobs provided for all bedroom and bathrooms. Entrance doors keyed alike. Dead bolts provided for one exterior door









INTERIOR FINISHES

- Pre-finished painted base and casing add the perfect finishing touch
- Walls and ceilings coated with an orange peel finish
- Bullnose Drywall corners
- · Tinted vapor barrier latex primer/finish, sprayed and rolled
- Plate glass beveled edge vanity mirrors

FLOOR COVERINGS

- Up to 40oz Plush Shaw Carpeting on 8lb pad in living room, hallways and bedrooms
- · All carpeted areas finished with a rolled edge
- Congoleum LuxFlor Vinyl Flooring in kitchen, bathrooms, dining, foyer, and laundry as indicated on plans



CABINETRY & COUNTERTOPS

- Timberline Signature Series Concord Style Painted Cabinetry featuring:
- Full Overlay door design
- Solid wood door frame with 2" stiles and rails
- Flat center panel door
- Doors and drawers have a 90° return and no reverse bevel
- Slab drawer front is solid wood
- Drawer Guides Full extension, Concealed, Under-mount, slide system with Soft Action
- · Soft Close Doors
- Crown Moulding on all upper cabinetry
- Cabinetry Hardware
- Tempo Edge Laminate Countertop with pre-formed 3" Backsplash

CLOSETS

- · Bedrooms one level of wood shelving, with built-in hanging rail
- · Linen three levels of wood shelving
- · Pantry five levels of wood shelving



Request a copy of our Platinum Series Plan Book to view our vast array of plans!